

(509) 927-8527
GENICS

CobraTM Plug

Plastic



9/16 x 2" Plugs

50pk	Black	30623
50pk	Brown	30632
50pk	Tan	30633
100pk	Black	30625
100pk	Brown	30635
100pk	Tan	30636

15/16 x 2" Plugs

100pk	Black	30685
100pk	Brown	30690
100pk	Tan	30691



- CobraTMPlugs are treated, reusable plugs used to re-seal test or bore hole openings on wood poles to prevent water and decay ingress.
- CobraTMPlugs are available in three sizes – 9/16" x 1 5/8", 13/16" x 2" and 15/16" x 2".
- CobraTMPlugs are impregnated with boron, a non-restricted-use pesticide providing treatment at bore-hole entrance.
- CobraTMPlugs are made of durable, high impact, UV-protected black nylon.
- CobraTMPlugs are also available in Brown and Tan to better match your wood structure.
- CobraTMPlugs are removable and reusable which allows for using the same hole for re-inspection and/or re-treatment thereby minimizing strength loss in the pole.
- CobraTMPlugs have an aggressive thread design providing a water tight seal.
- CobraTMPlugs have a strong, solid core which retain their shape.

Features:

- Tapered body
- Rounded exterior end
- Boron impregnated nylon
- Removable for reuse
- Aggressive thread design
- Quick twist in and out
- Solid core
- High impact nylon-UV protected
- Use special inspector key to remove
- Water tight seal
- Competitively priced

Benefits:

- Easy insertion - tight fit
- Removable even if over-hammered
- Imparts treatment at bore-hole entrance
- Use the same hole and plug again, minimize strength loss
- Hammer in without damage to hole surface
- Allows for inspection and reuse
- Retains shape for easier removal and insertion
- Rugged long-lasting materials – more durable than polyethylene
- Deeper throat increases surface contact for greater torque
- Prevents water ingress into bore-hole
- No negative budget impacts

Cobra™ Plug – 9/16” x 1 5/8”

- treated reusable plug used to re-seal 1/2” to 9/16” openings of test holes (Cobra™ Rod treatment holes) to prevent water and decay ingress.
- requires Genics CobraRod Inspector Key to remove plug.

Cobra™ Plug – 15/16” x 2”

- treated reusable plug is used to seal 7/8” to 15/16” openings of bore holes to prevent water and decay ingress.
- requires standard 3/8” socket drive to remove plug.

For Use With:

- Cobra™ Rod / PostGuard Rod – solid diffusible wood preservative rods
- Genics GenBor RTU-2 / Genics CuB Liquid Preservatives

